



SSL4	Solar Panel	40Wp	Mono crystalline silicon ,822x432x25 MM,5kg
	Controller	DC12V 5A	140x90x28 MM Intellective control Protection functions Adjustable brightness and lighting hour.
	LED lamp	DC12V 20 W	LED lights are integrated under the solar panel. Two optional colors of the Led's,yellow and white. Light beam:square,circular or elliptic Can be set to work at half efficiency
	Battery	12V,14AH, 2PC	151x98x95 MM,4.2 KG Sealed lead-acid maintenance-free battery Placed at the backrear of the light
	Height of the Pole	Applicable to the pole 4-6 mt.	
	Working Time	8 hours every day.Works 5 hours at full power,and 3 hours at half power Keeps normal working for 2 continuous cloudy and rainy days.	

SSL5	Solar Panel	40Wp	Mono crystalline silicon ,822x432x25 MM,5kg
	Controller	DC12V 5A	140x90x28 MM Intellective control Protection functions Adjustable brightness and lighting hour.
	LED lamp	DC12V 30 W	LED lights are integrated under the solar panel. Two optional colors of the Led's,yellow and white. Light beam:square,circular or elliptic Can be set to work at half efficiency
	Battery	12V,18AH, 2PCS	151x98x95 MM,4.2 KG/PC Sealed lead-acid maintenance-free battery Placed at the backrear of the light
	Height of the Pole	Applicable to the pole 6-8 mt.	
	Working Time	8 hours every day.Works 5 hours at full power,and 3 hours at half power Keeps normal working for 2 continuous cloudy and rainy days.	